FIBERGLASS ROD Ø 6 MM STANDARD-SET

with steel cage incl. new double-outlet system

Item no.: **10060** | **10062** | **10064** | **10066**

RUNPOTEC
STRONGEST CABLE PULLING

VIDEO

Fiberglass rod
Ø 6 mm

Achtung!
Stromleitend
Attention!
electric
conductive

Detailed images:

All steel cages are equipped with a lateral locking brake and the new double-outlet system (quick outlet and automatic run-out brake)

Quick run with rollers

automatic run-out brake

BEGINNING

RUNPOGLIDER with swivel Ø 7 mm, RUNPOTEC RTG Ø 6 mm thread - screwed to strand

ENDING

Ending joint, stainless steel, RUNPOTEC RTG Ø 6 mm thread

DATA	Recommended retail price / excluding VAT			
ITEM NO.	**10060**	**10062**	**10064**	**10066**
PRICE €	**233,10**	**257,25**	**285,60**	**344,40**
LENGTH	40 m	50 m	60 m	80 m
TOTAL WEIGHT KG	6,909	7,109	7,309	7,709
DIMENSION	H 548 / B 675 / T 250			
MATERIAL	Fiberglass core with PP sheath			
PIPE Ø	for tube diameter 40 - 100 mm			
TOTAL BREAKING LOAD	320 kg			

ADVANTAGES

- **incl. steel reel**
- **Double run-out system (automatic run-out brake and fast run-out)**
- **Additional parking brake**
- **Glass fibre rod total breaking load up to 2200 kg**
- **Total breaking load 320 kg**
- **Bending radius 168 mm**

Rec. tube diameter, bending radius and total breaking load for the fiberglass rod Ø 6 mm

Ø				
6 mm	40 - 100 mm	168 mm	2200 kg	320 kg

DESCRIPTION

Standard set glass-fibre rod Ø 6 mm - RUNPOTEC RTG Ø 6 mm thread with robust steel reel Ø 330 mm (galvanised/powder coated) with new, double run-out system (automatic run-out brake and fast run-out), additional parking brake. Glass fibre rod total breaking load 2200 kg, total breaking load 320 kg
Optimal field of application: for pipe diameters 40 mm - 100 mm.
Application video: a short, very informative application video can be viewed by scanning the QR code or on www.runpotec.com.
Scope of delivery: 1 piece fibreglass rod Ø 6 mm Profi Set incl. RUNPOGLEITER at the rod tip and end sleeve at the rod end

INFORMATION

USE WITH:

RUNPOCAM RC2
LENGTH: 10 m | 30 m | 50 m
Item no.: 10139 | 10140 | 10141

RUNPOTEC GmbH | Irlachstraße 31 | A-5303 Thalgau | Tel.: +43-6235-20335 | Fax: +43-6235-20335-35 | office@runpotec.com | www.runpotec.com
The images are representative. Changes and printing errors excepted - Revision: March 2020

FIBERGLASS ROD Ø 6 MM PROFI SET

with steel cage incl. new double-outlet system

Item no.: **10059 | 10061 | 10063 | 10065**

RUNPOTEC
STRONGEST CABLE PULLING

VIDEO

Fiberglass rod Ø 6 mm

Achtung! Stromleitend
Attention! electric conductive

INCL. ACCESSORIES

Detailed image

BEGINNING

RUNPOGLIDER with swivel Ø 7 mm, RUNPOTEC RTG Ø 6 mm thread - screwed to strand

ENDING

Ending joint, stainless steel, RUNPOTEC RTG Ø 6 mm thread

DATA	Recommended retail price / excluding VAT			
ITEM NO.	10059	10061	10063	10065
PRICE €	**283,50**	**307,65**	**336,00**	**394,80**
LENGTH	40 m	50 m	60 m	80 m
TOTAL WEIGHT KG	7,820	8,020	8,220	8,620
DIMENSION	H 570 / B 675/ T 250			
MATERIAL	Fiberglass core with PP sheath			
PIPE Ø	for tube diameter 40 - 100 mm			
TOTAL BREAKING LOAD	320 kg			

ADVANTAGES

- **incl. steel reel**
- **Double run-out system (automatic run-out brake and fast run-out)**
- **Additional parking brake**
- **Glass fibre rod total breaking load up to 2200 kg**
- **Total breaking load 320 kg**
- **Bending radius 168 mm**

Rec. tube diameter, bending radius and total breaking load for the fiberglass rod Ø 6 mm

Ø				
				
6 mm	40 - 100 mm	168 mm	2200 kg	320 kg

DESCRIPTION

Professional set glass-fibre rod Ø 6 mm - RUNPOTEC RTG Ø 6 mm thread with robust steel reel Ø 330 mm (galvanised/powder coated) with new, double run-out system (automatic run-out brake and fast run-out), additional parking brake, extendable feet and storage compartment for accessories. Glass fibre rod total breaking load 2200 kg, total breaking load 320 kg

Optimal field of application: for pipe diameters 40 mm - 100 mm.

Application video: a short, very informative application video can be viewed by scanning the QR code or on www.runpotec.com.

Scope of delivery: 1 piece fibreglass rod Ø 6 mm Profi Set incl. RUNPOGLEITER at the rod tip and end sleeve at the rod end, extendable feet and storage compartment + additional accessories: 2 x end sleeve,1 x connecting sleeve,1 x shackle,1 x special adhesive,1 x roller, 1 x RUNPOGLEITER with front thread

INFORMATION

USE WITH:

RUNPOCAM RC2

LENGTH: 10 m | 30 m | 50 m

Item no.: 10139 | 10140 | 10141

RUNPOTEC GmbH | Irlachstraße 31 | A-5303 Thalgau | Tel.: +43-6235-20335 | Fax: +43-6235-20335-35 | office@runpotec.com | www.runpotec.com

The images are representative. Changes and printing errors excepted - Revision: March 2020